

ELEVATION FRONT

Grate type- 1 300 see plans (12) min. Edge of pavement 356 (14) min. for 178 (7) opening Pavement 200 (8) thickness 20 (3/4) Mortar #15 (#4) bars 750 (30) Slope = 8%三柳美丁 75 (3) sand cushion ELEVATION SIDE

Set frame level and at elevation

of edge of pavement at the intersection of (of inlet frame.

GENERAL NOTES

Frame and grate

(See General Notes)

- 1. Inlet construction shall be in accordance with Section 602 of the Standard Specifications.
- 2. Combination Concrete Curb & Gutter shall be constructed in accordance with Section 606 of the Standard Specifications.
- 3. See District CADD Standard 604001-D4 for frame and grates.

All dimensions are in millimeters (inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD

DATE REVISIONS BY 1-1-97 RENUM. B-4.01, NEW REVISION BOX T.P. 10-99 REVISION TO GENERAL NOTES J.A. 2-00 REVISION TO DESIGNER NOTES J.A. INLETS, TYPE G-1

CADD STD NO. 602001-D4

SCALE NOT TO SCALE DRAWN BY CADD DATE \$6DATE\$

+DGN-ONLY+

~. Vi W 4. Vi

602001-D4